

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS

1. (original) A self-closing prestressed tubular belt with a longitudinal joint,
5 comprising:
 - a first layer having tension forces that are variable along its width; and
 - a second layer that is attached to the first layer having compression forces that are variable along its width, so that the belt will curl around an axis defined by a length of the belt with a predetermined shape and
10 a predetermined force at the longitudinal joint.
2. (original) The tubular belt according to claim 1, wherein:
 - the first layer is an inner elastic layer having an unstressed width that is less than its width in the tubular belt; and
 - 15 the second layer is an outer elastic layer having an unstressed width that is greater than its width in the tubular belt.
3. (original) The tubular belt according to claim 1, wherein the first layer comprises a central portion having tension forces that are variable along its
20 width, and a peripheral portion having no tension forces.
4. (original) The tubular belt according to claim 1, wherein the first layer has tension forces that are stepwise variable along its width in step regions, the tension forces in any step region being constant, and the tension forces in
25 adjacent step regions are different from one another.

5. (original) The tubular belt according to claim 1, wherein the first layer comprises one or more attached anchor strips that are configured to be in a force-holding relationship to a tool.

5 6. (currently amended) A self-closing prestressed tubular belt with a longitudinal joint, comprising:

a longitudinal axis that defines a longest dimension of the belt and is parallel with a direction of motion when the belt is used;

10 a transverse axis that defines a belt width that is perpendicular to the longitudinal axis when the belt is flattened, the belt having outer edges at the extremes of the transverse axis and having a central portion that is in between the outer edges but does not include the outer edges; and

15 a height axis that defines a belt thickness that is perpendicular to the longitudinal axis and the transverse axis;

a first layer that is prestressed; and

20 a second layer having a depression solely in the depressed central portion and along the longitudinal axis, the depression reducing the belt thickness along the height axis that is permanently filled with the first prestressed layer.

7. (currently amended) A self-closing prestressed tubular belt with a longitudinal joint, comprising:

25 a longitudinal axis that defines a longest dimension of the belt and is parallel with a direction of motion when the belt is used;

a transverse axis that defines a belt width that is perpendicular to the longitudinal axis when the belt is flattened, the belt having outer edges at the extremes of the transverse axis and having a central

portion that is in between the outer edges but does not include the outer edges; and

a height axis that defines a belt thickness that is perpendicular to the longitudinal axis and the transverse axis;

5 a first layer that is prestressed; and

a second layer having a central region, wherein the first layer is joined to the second layer only in the central region so that the central region of the two joined layers is thicker than either the first or second layer alone a peripheral region.

10

8. (currently amended) A self-closing prestressed tubular belt with a longitudinal joint, comprising:

a longitudinal axis that defines a longest dimension of the belt and is parallel with a direction of motion when the belt is used;

15

a transverse axis that defines a belt width that is perpendicular to the longitudinal axis when the belt is flattened, the belt having outer edges at the extremes of the transverse axis and having a central portion that is in between the outer edges but does not include the outer edges; and

20

a height axis that defines a belt thickness that is perpendicular to the longitudinal axis and the transverse axis;

a split zone on a lower portion of the belt when it is in an opened flattened state, wherein the belt is divided into one or more flaps along a dividing plane that is defined by the longitudinal axis and the transverse axis parallel to a surface of the belt, wherein a plane passing through a proximate edge of the one or more flaps attached to the belt and an opposite distal edge of the one or more flaps is parallel to the dividing plane.

25

9. (currently amended) ~~The tubular belt according to claim 8,~~

A self-closing prestressed tubular belt with a longitudinal joint, comprising:

a split zone on a lower portion of the belt wherein the belt is divided into
one or more flaps along a dividing plane parallel to a surface of the
5 belt;

wherein the flaps are located on a bottom portion of the belt, the tubular
belt further comprising an additional belt component used to fill a
gap between edges of the flaps, the gap being created by
prestressing of the belt in a direction parallel to a plane of the belt.

10

10. (original) A self-closing prestressed tubular belt with a longitudinal joint,
wherein a bending stiffness of the belt in a plane lying through an interlock of the
joint and a centroid of a section of the belt is equivalent to a similarly constructed
tubular belt having no longitudinal joint.

15

11. (original) A self-closing prestressed tubular belt with a longitudinal joint, the
belt being configured to be operable when bent along its route, the route having
a curvature radius of less than three hundred times a diameter of the belt.

20 12 - 26. (canceled).